

Marking segment n° 42



Benefits

- Especially versatile, since it is independent of the workpiece diameter
 - Exchangeable segments enable fast, flexible, and economical adaptation of the text for different applications
 - Marking is possible at high speed
 - Change of the reading direction is possible (see operating manual)
 - Exchangeable segment mount unit for faster switching to a different text
- Full depth and definition are accomplished in one go
 - All characters can be used as a drive, e.g. logos, backlash, asterisks, number signs, etc.
- ## Application
- Precise positioning of characters on workpiece circumference
 - Centre height corresponds to first marking point
 - Marking positions can be set as desired

Application

- ▢ Precise positioning of characters on workpiece circumference
- ▢ Centre height corresponds to first marking point
- ▢ Marking positions can be set as desired

Features

- The design of marking segment n° 42 is independent of the workpiece diameter
- Three driving points guarantee a perfect impression. They may be placed to the side of the characters
- Marking without driving points is generally possible

Standard design		For marking tools
Flank angle	90°	431
Dimensions (Ø x width x bore) [mm]	45 x 6 x 33	
Typeface	According to DIN 1451	
Max. character height	See "Technology" starting on page 20	

Order no. character height 2 mm	Order no. character height 3 mm	Segments designation
82000067		Start segment
82002237	82002300	Letter set A–Z
82000441	82000378	Numeral set 0–9
82000433	82000041	Special character . (dot)
82000879	82002230	Special character/(slash)
82000416	82000040	Special character – (minus)
82000065		End segment